

LLK - International
Manager of Industrial OEM Dept.
Mr. Stepan Kirillov

Your Ref.

Our Ref.

Date

04.09.2015

Contact

Phone

+49 (0) 6594.10-120

E-Mail

schermann@feluwa.de

LUKOIL lubricants use in Feluwa equipment

Dear Mr. Kirillov,

This letter is the official approval of LUKOIL lubricants, which meet the requirements for Feluwa pumps and gearboxes.

Oils that could be used in our pumps:

a) Hydraulic oil in pump heads

For the application in our pump heads hydraulic oil is used in the viscosity classes VG46 or VG68.

The use of LUKOIL GEYSER ST 46 or LUKOIL GEYSER ST 68 is permitted.

There are appropriate approvals.

b) Mineral gear oil in Feluwa stroke gears

For the purposes of our FELUWA stroke- and reduction gears we use mineral gear oils in the viscosity grades VG220 or VG320.

The use of LUKOIL STEELO VG220 or LUKOIL STEELO VG320 is permitted.

There are appropriate approvals. (acc. Flender T 7300)

c) Synthetic gear oil in intermediate gear (other manufactures)

If synthetic oil is required the use of synthetic gear oil LUKOIL OMV gear SHG 220 or LUKOIL OMV gear SHG 320 is permitted.

There are appropriate approvals. (acc. Flender T 7300)

Feluwa Pumpen GmbH


Dipl.-Ing. Ernst Schermann

Senior Service Engineer



FELUWA Pumpen GmbH
Beulertweg 10 | Germany
54570 Mürlenbach

Phone +49 (0) 6594.10-0
Fax +49 (0) 6594.10-200

info@feluwa.de
www.feluwa.com

Register

Wittlich HRB 12510

Managing Directors

Rudolf Gänsel
Markus Dönni

Chairman of the Advisory Board

Dr. Rüdiger Kaspers

Advising Partner

Heinz M. Nägel

ARCA Flow Group

Germany | Switzerland
The Netherlands | India
South Korea | P.R. China
Mexico

